

KORLOY Indexable new generation drill

KING DRILL



Optimized design of inserts for maximum drilling efficiency

- Excellent cutting performance and chip control due to the optimized geometry and chip breaker of both inserts, central & peripheral
- 2 different inserts, optimized for the central and peripheral insert locations in order to maximize cutting tool life




KING DRILL

Optimized insert design for maximum drilling efficiency

KING DRILL

Code system of holder



Features of insert

Optimized design of inserts for maximum drilling efficiency

- Excellent cutting performance and chip control due to the optimized geometry and chip breaker of both inserts, central & peripheral
- Different inserts, optimized for the central and peripheral insert locations in order to maximize cutting tool life

Chip breaker	PD		LD	
Insert	Peripheral insert	Central insert	Peripheral insert	Central insert
Features	- Universal - At medium speed and medium feed		- Superior chip control for machining mild steel and stainless steel - Light cutting(at low ~ medium speed and low feed)	
Shape				
Grades for workpiece	PC3500 : P PC5300 : P, M, K, S PC6510 : K	PC5300 : P, M, K, S	PC5335 : P, M	PC5335 : P, M


Features of drill



- The center coolant hole system helps prevent wear on the chip pocket of the central insert and improves chip control.
- The optimized shape of the flute increases the rigidity of the drill body and improves chip evacuation.

Machining performance

• Tool life comparison




- Workpiece SCM440
- Cutting condition $vc(m/min)=150$, $fn(mm/rev)=0.1$
Depth of drilling : 80mm(pass though), wet
- Tools Insert SPMT060205-PD(PC3500), XOMT060204-PD(PC5300)
Holder K5D18025-06

• KING DRILL has the best tool life.




- KING DRILL
320 Holes (28.8m)
Normal wear
- Competitor A
230 Holes (20.7m)
Chipping on cutting edge
- Competitor B
140 Holes (12.6m)
Wear and chipping on cutting edge

• Surface roughness





• Superior surface roughness of KING DRILL



- Workpiece SCM440
- Cutting condition $vc(m/min)=150$, $fn(mm/rev)=0.08$, Depth of drilling : 60mm(pass though), wet
- Tools Insert SPMT050204-PD(PC3500), XOMT050204-PD(PC5300)
Holder K5D14020-05

KING DRILL


Precision of machining



- Workpiece SCM440
- Cutting condition $vc(m/min)=150$, $fn(mm/rev)=0.08$
Depth of drilling 6m(pass though), wet
- Tools Insert SPMT050204-PD(PC3500),
XOMT050204-PD(PC5300)
Holder K5D14020-05

• The diameters of beginning, middle, and end of hole are regular after drilling with KING DRILL.

Chip evacuation




KING DRILL

- Stable chip control



Competitor A


- Thin and long chips are coiled around the holder.



Competitor B

- Folded chips under certain cutting condition
- Poor chip evacuation

Application examples




[workpiece]



- Superior surface finish and chip evacuation
- KING DRILL : 180ea, Competitor's : 120ea
- 150% longer tool life

- Workpiece Track link bush
- Cutting condition $vc(m/min)=120$, $fn(mm/rev)=0.1$
Through coolant system
- Tools Insert SPMT07T208-PD(PC3500), XOMT07T205-PD(PC5300)
- Machine Holder K5D20025-07
Drilling machine


• Example of longer tool life



• Workpiece	Hydraulic oil pump(SCM440)
• Cutting condition	$vc(m/min)=152$ $fn(mm/rev)=0.13$ $ap(mm)=59$ (not pass though) Through coolant system
• Tools	Insert SPMT090308-PD(PC3500) XOMT090305-PD(PC5300)
• Machine	Holder K3D25532-09 KV45

- Superior chip evacuation and surface finish
- 184% longer tool life comparing to competitor A
- 117% longer tool life comparing to competitor B


• Example of improved productivity



• Workpiece	Track link bush(SCM415H)
• Cutting condition	Competitor's $vc(m/min)=125$ $fn(mm/rev)=0.1$
• Tools	Korloy's $vc(m/min)=140$ $fn(mm/rev)=0.12$
• Machine	Insert SPMT090308-PD(PC3500) XOMT090305-PD(PC5300)
	Holder K3D27025-09 MCT

- KING DRILL : 95 Holes, Competitor : 70 Holes, 135% longer tool life
- 135% improved productivity

• Example of improved productivity and tool life



Chips from KING DRILL



Chips from competitor's

• Workpiece	Track link(15b36C12)
• Cutting condition	Competitor's $vc(m/min)=47$, $fn(mm/rev)=0.1$, Through coolant system
	Korloy's $vc(m/min)=110$, $fn(mm/rev)=0.1$, Through coolant system
• Tools	Insert SPMT090308-PD(PC3500), XOMT090305-PD(PC5300)
	Holder K3D27025-09
• Machine	MCT

- KING DRILL has 145% longer tool life and 200% improved productivity.
- Good surface finish, improved chip control and less chattering

KING DRILL

Recommended cutting condition

(mm)


Workpiece			Grade		VC	Feed(aspect ratio=2D, 3D, 4D)					
						Feed (mm/rev) depending on drill Dia.(mm)					
ISO	Workpiece	Hardness(HB)	m/min		12~16	17~23	24~29	30~42	43~60		
P	Carbon steel	Low carbon steel	80~180	LD	Central insert PC5335 Peripheral insert	150(60~180)	0.04~0.08	0.04~0.08	0.04~0.08	0.04~0.08	0.04~0.08
				PD	Central insert PC5300 Peripheral insert PC3500	190(130~250)					
	High carbon	180~280	PD	Central insert PC5300 Peripheral insert PC3500	140(80~200)	0.04~0.10	0.04~0.12	0.05~0.16	0.08~0.18	0.10~0.22	
	Alloy steel	Low alloy steel	140~260	LD	Central insert PC5335 Peripheral insert	150(60~180)	0.04~0.10	0.04~0.10	0.04~0.12	0.04~0.14	0.04~0.14
				PD	Central insert PC5300 Peripheral insert PC3500	150(90~200)	0.06~0.12	0.06~0.12	0.06~0.14	0.06~0.16	0.06~0.16
		Hardened low alloy steel	200~400	PD	Central insert PC5300 Peripheral insert PC5300	100(50~150)	0.04~0.10	0.06~0.12	0.08~0.16	0.08~0.18	0.08~0.22
		High alloy steel	50~260	PD	Central insert PC5300 Peripheral insert PC3500	100(50~160)	0.04~0.18	0.06~0.12	0.08~0.16	0.08~0.18	0.08~0.22
		Hardened high alloy steel	220~450	PD	Central insert PC5300 Peripheral insert PC5300	70(30~120)	0.04~0.12	0.06~0.14	0.08~0.17	0.08~0.17	0.08~0.20
M	Stainless steel	Austenite series	135-275	LD	Central insert PC5335 Peripheral insert	90(40~150)	0.04~0.10	0.04~0.12	0.04~0.12	0.04~0.12	0.04~0.12
				PD	Central insert PC5300 Peripheral insert PC5300		0.04~0.10	0.06~0.12	0.06~0.14	0.06~0.16	0.06~0.20
		Ferrite series Martensite series	135~275	LD	Central insert PC5335 Peripheral insert	100(60~160)	0.04~0.10	0.04~0.12	0.04~0.12	0.04~0.12	0.04~0.12
				PD	Central insert PC5300 Peripheral insert PC5300		0.04~0.10	0.04~0.12	0.06~0.14	0.06~0.14	0.06~0.14
K	Cast iron	Gray cast iron	150~230	PD	Central insert PC5300 Peripheral insert PC6510	190(150~250)	0.04~0.10	0.05~0.14	0.06~0.18	0.10~0.22	0.10~0.26
		Ductile cast iron	150~230	PD	Central insert PC5300 Peripheral insert PC6510	150(100~200)	0.04~0.10	0.04~0.12	0.04~0.14	0.05~0.16	0.05~0.18
S	Heat resisting alloy	Ni-heat resisting alloy	130~400	PD	PC5300	50(30~100)	0.04~0.06	0.04~0.08	0.04~0.10	0.06~0.12	0.06~0.12
		Ti-heat resisting alloy	130~400	PD	PC5300	40(30~90)	0.04~0.08	0.04~0.10	0.06~0.12	0.08~0.14	0.08~0.16
		High hardened steel	Over 400	PD	PC5300	40(20~80)	0.04~0.08	0.06~0.12	40(20~80)	0.08~0.14	0.08~0.16

- In case of 5D, reduce 30~40% of cutting condition from the above.


- In interrupted machining part, reduce 30~50% of feed from the above machining around interrupted part.

Required machine power

- The graphs below show the cutting force required in drilling.
- Machining with the KING DRILL and a machine with high rigidity and power



Cutting oil quantity





• Workpiece : SCM440(240HB)
 • Cutting condition : $v_c(m/min)=100$
 • Through coolant system

- Recommended pressure of coolant : 5kg/cm² above
- The data of the graph above could be changed depending on workpiece and cutting condition.



Drill tolerance and hole tolerance



(mm)

Drill diameter		Ø12 ~ Ø29	Ø30 ~ Ø45	Ø46 ~ Ø60.5
2D~3D	Drill tolerance(ØD)	0 ~ -0.15	0 ~ -0.15	0 ~ -0.15
	Hole tolerance	+0.2 ~ -0.1	+0.25 ~ -0.1	+0.28 ~ -0.1
4D~5D	Drill tolerance(ØD)	0 ~ -0.15	0 ~ -0.15	0 ~ -0.15
	Hole tolerance	+0.25 ~ -0.05	+0.3 ~ -0.05	+0.33 ~ -0.05


- The actual hole tolerance of KING DRILL is as shown in the chart above.
- The length of drill, kind of workpiece, machine stability, and cutting condition could affect the hole tolerance.

KING DRILL


The shape of the bottom of blind hole

Drill diameter(mm)	Peripheral insert	Central insert	a
Ø12.0~Ø13.5	SPMT040204-□□	XOMT040204-□□	0.4
Ø13.6~Ø16.0	SPMT050204-□□	XOMT050204-□□	0.4
Ø16.1~Ø19.5	SPMT060205-□□	XOMT060204-□□	0.5
Ø19.6~Ø23.5	SPMT07T208-□□	XOMT07T205-□□	0.5
Ø23.6~Ø29.5	SPMT090308-□□	XOMT090305-□□	0.7
Ø29.6~Ø35.5	SPMT11T308-□□	XOMT11T306-□□	0.8
Ø35.6~Ø42.5	SPMT130410-□□	XOMT130406-□□	1.0
Ø42.6~Ø50.5	SPMT15M510-□□	XOMT15M508-□□	1.1
Ø50.6~Ø60.5	SPMT180510-□□	XOMT180508-□□	1.2

- KING DRILL drills with two inserts, central and peripheral
- Refer to the above chart for remaining insert curve of blind hole bottom.




How to clamp KING DRILL to side lock arbor



- Recommendation to use side lock arbor for KING DRILL
1. Insert the part of side lock of drill to the same direction of clamping the bolt to the arbor
 2. Push the plunge side of drill into the arbor.
 3. Clamp the bolt 1 first.
 4. Next, clamp the bolt 2.

Notice for setting the drill in the lathe






- Set the peripheral insert parallel to the X axis. (based on the side lock)
- If the machined core is 0.5mm after machining 5mm, that is the proper setting.

* Please make sure that the location of the side lock could be different depending on manufacturers of machine.

KING DRILL

Machining required attention

Workpiece	Machining	
	Machining irregular face	<ul style="list-style-type: none"> Possible chipping and fracture of the insert Reduce normal feed 25%.
	Machining convex side	<ul style="list-style-type: none"> Possible initial contact with central insert Reduce feed 50% until both inserts are engaged.
	Machining concave side	<ul style="list-style-type: none"> Reduce feed 50% until both inserts are engaged.
	Boring	<ul style="list-style-type: none"> Reduce feed 50% from normal conditions.
	Ramping	<ul style="list-style-type: none"> Reduce feed 50% from normal conditions.
	Machining cross holes	<ul style="list-style-type: none"> Reduce feed 50% in the overlapped section.
	Machining overlapped holes	<ul style="list-style-type: none"> Reduce feed 50% from normal conditions.
	Machining overlapped panels	<ul style="list-style-type: none"> Possible chipping and fracture of insert Reduce normal feed 25%.

Solutions for machining failure

Failure	Detail	Solution
Different diameters of one machined hole	Different diameters of one machined hole → The end of hole diameter is bigger.	<ul style="list-style-type: none"> • Use more coolant and check the coolant evacuation. • Change the drill to one with small aspect ratio. • Change the cutting condition for better chip control.
Enlarging or reducing hole diameter	Enlarging or reducing hole diameter	<ul style="list-style-type: none"> • Milling → Use more coolant. → Check the coolant evacuation. • Turning → Check the center of drill and workpiece. → Rotate the drill to 180°.
Chattering	Vibration while machining	<ul style="list-style-type: none"> • Set the overhang of drill short. • Reduce the cutting speed and feed. • Stable clamping • Check the torque of machine.
Poor chip evacuation	Long chip	<ul style="list-style-type: none"> • Mild steel / STS → speed up, feed down.
		<ul style="list-style-type: none"> • Alloy steel / carbon steel → speed up, feed up.
	Short chip	<ul style="list-style-type: none"> • Speed down, feed down, pressure of coolant up.
Poor surface finish	Scratch on the machined side	<ul style="list-style-type: none"> • Set the cutting condition for better chip control. • Feed down or speed up. • Increase the coolant flow and check the coolant evacuation. • Set the overhang of drill short and more stable clampin.
Short tool life of insert	Too much wear or chipping on insert	<ul style="list-style-type: none"> • Check the cutting condition. • Use more coolant and check the coolant evacuation. • Set the overhang of drill short and more stable clamping. • Change the insert grade.






Insert and parts

Drill diameter	Peripheral insert	Central insert	Screw	Wernch	Torque(㎏·m)
Ø12.0~Ø13.5	SPMT040204-□□	XOMT040204-□□	FTNA0204	TW06P	0.4
Ø13.6~Ø16.0	SPMT050204-□□	XOMT050204-□□	FTNA0204	TW06P	0.4
Ø16.1~Ø19.5	SPMT060205-□□	XOMT060204-□□	FTKA02206S	TW07P	0.8
Ø19.6~Ø23.5	SPMT07T208-□□	XOMT07T205-□□	FTKA02565	TW07S	0.8
Ø23.6~Ø29.5	SPMT090308-□□	XOMT090305-□□	FTKA0307	TW09S	1.2
Ø29.6~Ø35.5	SPMT11T308-□□	XOMT11T306-□□	FTKA03508	TW15S	3
Ø35.6~Ø42.5	SPMT130410-□□	XOMT130406-□□	FTKA0410	TW15S	3
Ø42.6~Ø50.5	SPMT15M510-□□	XOMT15M508-□□	FTNC04511	TW20S	5
Ø50.6~Ø60.5	SPMT180510-□□	XOMT180508-□□	FTNA0511	TW20-100	5

- In clamping an insert, please clean the tip seat and apply CASMOLY1000 on the screw.
- Please make sure to use a Korloy-produced wrench and screw only.

KING DRILL

Special drill order form (Mark 'V' in the box)




Note

- Currently using tool :
- Current cutting condition
 - RPM or vc(m/min) :
 - vf(mm/min) or fn(mm/rev) :
 - Depth of cut(mm) :
- standard of measuring tool life :
- Currently using machine
 - Machining center :
 - General lathe :
 - CNC lathe :

Coolant type


- Oil hole on the plunge part
- Oil hole on the shank



Hole type


- Blind hole
- Thru hole

Types of shank




Location of side lock


- Parallel to peripheral insert(standard)




- 90° angle to peripheral insert



- 150° angle to peripheral insert




- 180° angle to peripheral insert



Drill with through coolant system for general lathe and CNC lathe without through coolant system


KING DRILL (for through coolant system with a lathe)

- Through coolant system with drill holder, plug, oil-hole hose and oil-hole pump
- PT Tap in the plug is combined to PT Tap connected to oil hose.
- Available to use the drill without a plug in milling machine



- Clamping oil hose to the bottom of plug and connect the oil pump to the holder

Designation	Diameter	Shank Dia.	M x p	Plug
K□D120~16020HP-□□	Ø12.0 ~ Ø16.0	Ø20	M12 x 1.5	PLG12PT18
K□D161~23525HP-□□	Ø16.1 ~ Ø23.5	Ø25	M16 x 1.5	PLG16PT18
K□D236~35532HP-□□	Ø23.6 ~ Ø35.5	Ø32	M20 x 2.0	PLG20PT14
K□D356~60940HP-□□	Ø35.6 ~ Ø60.5	Ø40	M27 x 2.0	PLG27PT38



- Plug is assembled.


Plug Type	M x p (Metric)	PT Tap	A
PLG12PT18	M12 x 1.5	1/8	16
PLG16PT18	M16 x 1.5	1/8	19
PLG20PT14	M20 x 2.0	1/4	26
PLG27PT38	M27 x 2.0	3/8	35

KING DRILL


High rigidity drill produces cost efficiency due to cartridge replacement.

KING DRILL (for large diameter drilling)

- Cartridge type for Ø61~Ø100 drilling
- Peripheral cartridge can adjust the drilling diameter within 5mm.
- Easy to adjust drilling diameter with adjusting bolt



• Adjustment of drill diameter




Adjustment(mm) Ø(mm)	Adjusting Washer	
	Designation	Width(mm)
1	WA0305	0.5
2	WA0310	1.0
3	WA0305 + WA0310	1.5
4	WA0310 x 2	2.0
5	WA0305 + WA0310 x 2	2.5

* Adjusting washer adjusts the drilling diameter within 5mm.




Insert

• SPMT-LD




• SPMT-PD




(mm)

Drill diameter	Designation		Grade	<i>l</i>	<i>t</i>	<i>r</i>	<i>d₁</i>
Ø16.1 ~ Ø19.5	SPMT	060205-LD	PC5335	6.2	2.5	0.5	2.5
Ø19.6 ~ Ø23.5		07T208-LD		7.5	2.8	0.7	2.8
Ø23.6 ~ Ø29.5		090308-LD		9.2	3.3	0.8	3.4
Ø29.6 ~ Ø35.5		11T308-LD		11.0	4.0	0.8	4.0
Ø35.6 ~ Ø42.5		130410-LD		13.0	4.5	1.0	4.5
Ø42.6 ~ Ø50.5		15M510-LD		15.2	5.0	1.0	5.5
Ø50.6 ~ Ø60.5		180510-LD		18.2	5.5	1.0	6.0
Ø12.0 ~ Ø13.5	SPMT	040204-PD	PC5300	4.7	2.4	0.4	2.3
Ø13.6 ~ Ø16.0		050204-PD		5.1	2.4	0.4	2.3
Ø16.1 ~ Ø19.5		060205-PD		6.2	2.5	0.5	2.5
Ø19.6 ~ Ø23.5		07T208-PD		7.5	2.8	0.7	2.8
Ø23.6 ~ Ø29.5	PC3500	090308-PD	PC6510	9.2	3.3	0.8	3.4
Ø29.6 ~ Ø35.5		11T308-PD		11.0	4.0	0.8	4.0
Ø35.6 ~ Ø42.5		130410-PD		13.0	4.5	1.0	4.5
Ø42.6 ~ Ø50.5		15M510-PD		15.2	5.0	1.0	5.5
Ø50.6 ~ Ø60.5	PC6510	180510-PD		18.2	5.5	1.0	6.0

• XOMT-LD



• XOMT-PD





(mm)

Drill diameter	Designation		Grade	<i>l</i>	<i>d</i>	<i>t</i>	<i>r</i>	<i>d₁</i>
Ø16.1 ~ Ø19.5	XOMT	060204-LD	PC5335	5.8	6.6	2.5	0.4	2.5
Ø19.6 ~ Ø23.5		07T205-LD		6.9	7.8	2.8	0.5	2.8
Ø23.6 ~ Ø29.5		090305-LD		8.4	9.6	3.3	0.5	3.4
Ø29.6 ~ Ø35.5		11T306-LD		10.0	11.4	4.0	0.6	4.0
Ø35.6 ~ Ø42.5		130406-LD		11.9	13.6	4.5	0.6	4.5
Ø42.6 ~ Ø50.5		15M508-LD		13.9	15.9	5.0	0.8	5.5
Ø50.6 ~ Ø60.5		180508-LD		16.5	18.9	5.5	0.8	6.0
Ø12.0 ~ Ø13.5	XOMT	040204-PD	PC5300	4.3	4.9	2.4	0.4	2.3
Ø13.6 ~ Ø16.0		050204-PD		4.8	5.4	2.4	0.4	2.3
Ø16.1 ~ Ø19.5		060204-PD		5.8	6.6	2.5	0.4	2.5
Ø19.6 ~ Ø23.5		07T205-PD		6.9	7.8	2.8	0.5	2.8
Ø23.6 ~ Ø29.5		090305-PD		8.4	9.6	3.3	0.5	3.4
Ø29.6 ~ Ø35.5		11T306-PD		10.0	11.4	4.0	0.6	4.0
Ø35.6 ~ Ø42.5		130406-PD		11.9	13.6	4.5	0.6	4.5
Ø42.6 ~ Ø50.5		15M508-PD		13.9	15.9	5.0	0.8	5.5
Ø50.6 ~ Ø60.5		180508-PD		16.5	18.9	5.5	0.8	6.0

KING DRILL



KING DRILL-2D



(mm)

Designatón	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K2D	12020-04	12.0	20	25	27	50	91	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	12520-04	12.5	20	25	27	50	91			
	13020-04	13.0	20	25	29	50	93			
	13520-04	13.5	20	25	29	50	93			
	14020-05	14.0	20	25	31	50	96			
	14520-05	14.5	20	25	31	50	96			
	15020-05	15.0	20	25	33	50	99			
	15520-05	15.5	20	25	33	50	99			
	16020-05	16.0	20	25	35	50	101			
	16525-06	16.5	25	34	35	56	107			
K2D	17025-06	17.0	25	34	37	56	109	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
	17525-06	17.5	25	34	37	56	109			
	18025-06	18.0	25	34	39	56	112			
	18525-06	18.5	25	34	39	56	112			
	19025-06	19.0	25	34	41	56	114			
	19525-06	19.5	25	34	41	56	114			
	20025-07	20.0	25	34	43	56	118			
	20525-07	20.5	25	34	43	56	118			
	21025-07	21.0	25	34	45	56	120			
	21525-07	21.5	25	34	45	56	120			
K2D	22025-07	22.0	25	34	47	56	122	SPMT07T208-PD XOMT07T205-PD	FTKA02565	TW07S
	22525-07	22.5	25	34	47	56	122			
	23025-07	23.0	25	34	49	56	126			
	23525-07	23.5	25	34	49	56	126			
	24032-09	24.0	32	44	51	60	133			
	24532-09	24.5	32	44	51	60	133			
	25032-09	25.0	32	44	53	60	135			
	25532-09	25.5	32	44	53	60	135			
	26032-09	26.0	32	44	55	60	137			
	26532-09	26.5	32	44	55	60	137			
K2D	27032-09	27.0	32	44	57	60	140	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
	27532-09	27.5	32	44	57	60	140			
	28032-09	28.0	32	44	59	60	143			
	28532-09	28.5	32	44	59	60	143			
	29032-09	29.0	32	44	61	60	145			
	29532-09	29.5	32	44	61	60	145			

KING DRILL-2D





(mm)

Designatlon	ØD	Ød_1	Ød_2	l_1	l_2	L	Insert	Screw	Wrech
K2D	30032-11	30.0	32	44	63	60	150	SPMT11T308-PD XOMT11T306-PD	FTKA03508
	30532-11	30.5	32	44	63	60	150		
	31032-11	31.0	32	44	65	60	152		
	31532-11	31.5	32	44	65	60	152		
	32032-11	32.0	32	44	67	60	154		
	32532-11	32.5	32	44	67	60	154		
	33032-11	33.0	32	44	69	60	157		
	33532-11	33.5	32	44	69	60	157		
	34032-11	34.0	32	44	71	60	159		
	34532-11	34.5	32	44	71	60	159		
	35032-11	35.0	32	44	73	60	161		
	35532-11	35.5	32	44	73	60	161		
	36040-13	36.0	40	48	76	70	176		
	36540-13	36.5	40	48	76	70	176		
	37040-13	37.0	40	48	78	70	178		
	37540-13	37.5	40	48	78	70	178		
	38040-13	38.0	40	48	80	70	181		
	38540-13	38.5	40	48	80	70	181		
	39040-13	39.0	40	48	82	70	183		
	39540-13	39.5	40	48	82	70	183		
	40040-13	40.0	40	48	84	70	186	SPMT130410-PD XOMT130406-PD	FTKA0410
	40540-13	40.5	40	48	84	70	186		
	41040-13	41.0	40	48	86	70	188		
	41540-13	41.5	40	48	86	70	188		
	42040-13	42.0	40	48	88	70	191		
	42540-13	42.5	40	48	88	70	191		
	43040-15	43.0	40	58	91	70	196		
	43540-15	43.5	40	58	91	70	196		
	44040-15	44.0	40	58	93	70	198		
	44540-15	44.5	40	58	93	70	198		
	45040-15	45.0	40	58	95	70	201	SPMT15M510-PD XOMT15M508-PD	FTNC04511
	45540-15	45.5	40	58	95	70	201		
	46040-15	46.0	40	58	97	70	203		
	46540-15	46.5	40	58	97	70	203		
	47040-15	47.0	40	58	99	70	206		
	47540-15	47.5	40	58	99	70	206		

KING DRILL



KING DRILL-2D



(mm)

Designatton	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K2D	48040-15	48.0	40	58	101	70	208	SPMT15M510-PD XOMT15M508-PD	FTNC04511	TW20S
	48540-15	48.5	40	58	101	70	208			
	49040-15	49.0	40	58	103	70	210			
	49540-15	49.5	40	58	103	70	210			
	50040-15	50.0	40	58	105	70	212			
	50540-15	50.5	40	58	105	70	212			
	51040-18	51.0	40	68	108	70	218			
	51540-18	51.5	40	68	108	70	218			
	52040-18	52.0	40	68	110	70	220			
	52540-18	52.5	40	68	110	70	220			
	53040-18	53.0	40	68	112	70	222			
	53540-18	53.5	40	68	112	70	222			
	54040-18	54.0	40	68	114	70	224			
	54540-18	54.5	40	68	114	70	224			
	55040-18	55.0	40	68	116	70	226			
	55540-18	55.5	40	68	116	70	226			
	56040-18	56.0	40	68	118	70	230	SPMT180510-PD XOMT180508-PD	FTNA0511	TW20-100
	56540-18	56.5	40	68	118	70	230			
	57040-18	57.0	40	68	121	70	233			
	57540-18	57.5	40	68	121	70	233			
	58040-18	58.0	40	68	124	70	236			
	58540-18	58.5	40	68	124	70	236			
	59040-18	59.0	40	68	127	70	239			
	59540-18	59.5	40	68	127	70	239			
	60040-18	60.0	40	68	130	70	242			
	60540-18	60.5	40	68	130	70	242			

KING DRILL-3D





(mm)

Designatón	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K3D	12020-04*	12.0	20	25	39	50	103	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	12220-04	12.2	20	25	39	50	103			
	12520-04	12.5	20	25	39	50	103			
	12920-04	12.9	20	25	42	50	106			
	13020-04	13.0	20	25	42	50	106			
	13520-04	13.5	20	25	42	50	106			
	14020-05*	14.0	20	25	45	50	110			
	14520-05	14.5	20	25	45	50	110			
	15020-05	15.0	20	25	48	50	114			
	15520-05*	15.5	20	25	48	50	114			
K3D	16020-05	16.0	20	25	51	50	117	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
	16525-06	16.5	25	34	51	56	123			
	17025-06	17.0	25	34	54	56	126			
	17525-06*	17.5	25	34	54	56	126			
	18025-06	18.0	25	34	57	56	130			
	18525-06	18.5	25	34	57	56	130			
	19025-06	19.0	25	34	60	56	133			
	19525-06*	19.5	25	34	60	56	133			
	20025-07	20.0	25	34	63	56	138			
	20525-07	20.5	25	34	63	56	138			
K3D	21025-07*	21.0	25	34	66	56	141	SPMT07T208-PD XOMT07T205-PD	FTKA02206S	TW07P
	21525-07	21.5	25	34	66	56	141			
	22025-07	22.0	25	34	69	56	144			
	22525-07	22.5	25	34	69	56	144			
	23025-07	23	25	34	72	56	149			
	23525-07	23.5	25	34	72	56	149			
	24032-09*	24.0	32	44	75	60	157			
	24532-09	24.5	32	44	75	60	157			
	25032-09	25.0	32	44	78	60	160			
	25532-09	25.5	32	44	78	60	160			
K3D	26032-09	26.0	32	44	81	60	163	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
	26532-09*	26.5	32	44	81	60	163			
	27032-09	27.0	32	44	84	60	167			
	27532-09	27.5	32	44	84	60	167			
	28032-09	28.0	32	44	87	60	171			
	28532-09	28.5	32	44	87	60	171			
	29032-09*	29.0	32	44	90	60	174			
	29532-09	29.5	32	44	90	60	174			

The items marked * can machine a tap foundation hole.

KING DRILL

KING DRILL-3D





(mm)

Designatton	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K3D	30032-11*	30.0	32	44	93	60	180	SPMT11T308-PD XOMT11T306-PD	FTKA03508
	30532-11	30.5	32	44	93	60	180		
	31032-11	31.0	32	44	96	60	183		
	31532-11	31.5	32	44	96	60	183		
	32032-11	32.0	32	44	99	60	186		
	32532-11	32.5	32	44	99	60	186		
	33032-11	33.0	32	44	102	60	190		
	33532-11	33.5	32	44	102	60	190		
	34032-11	34.0	32	44	105	60	193		
	34532-11	34.5	32	44	105	60	193		
	35032-11*	35.0	32	44	108	60	196		
	35532-11	35.5	32	44	108	60	196		
	36040-13	36.0	40	48	112	70	212		
	36540-13	36.5	40	48	112	70	212		
	37040-13	37.0	40	48	115	70	215		
	37540-13	37.5	40	48	115	70	215		
	38040-13	38.0	40	48	118	70	219		
	38540-13	38.5	40	48	118	70	219		
	39040-13	39.0	40	48	121	70	222		
	39540-13	39.5	40	48	121	70	222		
	40040-13	40.0	40	48	124	70	226	SPMT130410-PD XOMT130406-PD	FTKA0410
	40540-13	40.5	40	48	124	70	226		
	41040-13	41.0	40	48	127	70	229		
	41540-13	41.5	40	48	127	70	229		
	42040-13	42.0	40	48	130	70	233		
	42540-13	42.5	40	48	130	70	233		
	43040-15	43.0	40	58	134	70	239		
	43540-15	43.5	40	58	134	70	239		
	44040-15	44.0	40	58	137	70	242		
	44540-15	44.5	40	58	137	70	242		
	45040-15	45.0	40	58	140	70	246		
	45540-15	45.5	40	58	140	70	246		
	46040-15	46.0	40	58	143	70	249		
	46540-15	46.5	40	58	143	70	249		
	47040-15	47.0	40	58	146	70	253		
	47540-15	47.5	40	58	146	70	253		
	48040-15	48.0	40	58	149	70	256		
	48540-15	48.5	40	58	149	70	256		

The items marked * can machine a tap foundation hole.

KING DRILL-3D





(mm)

Designatton		ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K3D	49040-15	49.0	40	58	152	70	259	SPMT15M510-PD XOMT15M508-PD	FTNC04511	TW20S
	49540-15	49.5	40	58	152	70	259			
	50040-15	50.0	40	58	155	70	262			
	50540-15	50.5	40	58	155	70	262			
	51040-18	51.0	40	68	159	70	269			
	51540-18	51.5	40	68	159	70	269			
	52040-18	52.0	40	68	162	70	272			
	52540-18	52.5	40	68	162	70	272			
	53040-18	53.0	40	68	165	70	275			
	53540-18	53.5	40	68	165	70	275			
	54040-18	54.0	40	68	168	70	278			
	54540-18	54.5	40	68	168	70	278			
	55040-18	55.0	40	68	171	70	281			
	55540-18	55.5	40	68	171	70	281			
	56040-18	56.0	40	68	174	70	286			
	56540-18	56.5	40	68	174	70	286			
	57040-18	57.0	40	68	178	70	290			
	57540-18	57.5	40	68	178	70	290			
	58040-18	58.0	40	68	182	70	294			
	58540-18	58.5	40	68	182	70	294			
	59040-18	59.0	40	68	186	70	298			
	59540-18	59.5	40	68	186	70	298			
	60040-18	60.0	40	68	190	70	302			
	60540-18	60.5	40	68	190	70	302			

KING DRILL



KING DRILL-4D



(mm)

Designatón	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K4D	12020-04	12.0	20	25	51	50	115	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	12520-04	12.5	20	25	51	50	115			
	13020-04	13.0	20	25	55	50	119			
	13520-04	13.5	20	25	55	50	119			
	14020-05	14.0	20	25	59	50	124			
	14520-05	14.5	20	25	59	50	124			
	15020-05	15.0	20	25	63	50	129			
	15520-05	15.5	20	25	63	50	129			
	16020-05	16.0	20	25	67	50	133			
	16525-06	16.5	25	34	67	56	139			
K4D	17025-06	17.0	25	34	71	56	143	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
	17525-06	17.5	25	34	71	56	143			
	18025-06	18.0	25	34	75	56	148			
	18525-06	18.5	25	34	75	56	148			
	19025-06	19.0	25	34	79	56	152			
	19525-06	19.5	25	34	79	56	152			
	20025-07	20.0	25	34	83	56	158			
	20525-07	20.5	25	34	83	56	158			
	21025-07	21.0	25	34	87	56	162			
	21525-07	21.5	25	34	87	56	162			
K4D	22025-07	22.0	25	34	91	56	166	SPMT07T208-PD XOMT07T205-PD	FTKA02565	TW07S
	22525-07	22.5	25	34	91	56	166			
	23025-07	23.0	25	34	95	56	172			
	23525-07	23.5	25	34	95	56	172			
	24032-09	24.0	32	44	99	60	181			
	24532-09	24.5	32	44	99	60	181			
	25032-09	25.0	32	44	103	60	185			
	25532-09	25.5	32	44	103	60	185			
	26032-09	26.0	32	44	107	60	189			
	26532-09	26.5	32	44	107	60	189			
K4D	27032-09	27.0	32	44	111	60	194	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
	27532-09	27.5	32	44	111	60	194			
	28032-09	28.0	32	44	115	60	199			
	28532-09	28.5	32	44	115	60	199			
	29032-09	29.0	32	44	119	60	203			
	29532-09	29.5	32	44	119	60	203			

KING DRILL-4D





(mm)

Designatton	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K4D	30032-11	30.0	32	44	123	60	210	SPMT11T308-PD XOMT11T306-PD	FTKA03508
	30532-11	30.5	32	44	123	60	210		
	31032-11	31.0	32	44	127	60	214		
	31532-11	31.5	32	44	127	60	214		
	32032-11	32.0	32	44	131	60	218		
	32532-11	32.5	32	44	131	60	218		
	33032-11	33.0	32	44	135	60	223		
	33532-11	33.5	32	44	135	60	223		
	34032-11	34.0	32	44	139	60	227		
	34532-11	34.5	32	44	139	60	227		
	35032-11	35.0	32	44	143	60	231		
	35532-11	35.5	32	44	143	60	231		
	36040-13	36.0	40	48	148	70	248		
	36540-13	36.5	40	48	148	70	248		
	37040-13	37.0	40	48	152	70	252		
	37540-13	37.5	40	48	152	70	252		
	38040-13	38.0	40	48	156	70	257		
	38540-13	38.5	40	48	156	70	257		
	39040-13	39.0	40	48	160	70	261		
	39540-13	39.5	40	48	160	70	261		
	40040-13	40.0	40	48	164	70	266	SPMT130410-PD XOMT130406-PD	FTKA0410
	40540-13	40.5	40	48	164	70	266		
	41040-13	41.0	40	48	168	70	270		
	41540-13	41.5	40	48	168	70	270		
	42040-13	42.0	40	48	172	70	275		
	42540-13	42.5	40	48	172	70	275		
	43040-15	43.0	40	58	177	70	282		
	43540-15	43.5	40	58	177	70	282		
	44040-15	44.0	40	58	181	70	286		
	44540-15	44.5	40	58	181	70	286		
	45040-15	45.0	40	58	185	70	291		
	45540-15	45.5	40	58	185	70	291	SPMT15M510-PD XOMT15M508-PD	FTNC04511
	46040-15	46.0	40	58	189	70	295		
	46540-15	46.5	40	58	189	70	295		
	47040-15	47.0	40	58	193	70	300		
	47540-15	47.5	40	58	193	70	300		

KING DRILL



KING DRILL-4D



(mm)

Designatón	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K4D	48040-15	48.0	40	58	197	70	304	SPMT15M510-PD XOMT15M508-PD	FTNC04511	TW20S
	48540-15	48.5	40	58	197	70	304			
	49040-15	49.0	40	58	201	70	308			
	49540-15	49.5	40	58	201	70	308			
	50040-15	50.0	40	58	205	70	312			
	50540-15	50.5	40	58	205	70	312			
	51040-18	51.0	40	68	210	70	320			
	51540-18	51.5	40	68	210	70	320			
	52040-18	52.0	40	68	214	70	324			
	52540-18	52.5	40	68	214	70	324			
	53040-18	53.0	40	68	218	70	328			
	53540-18	53.5	40	68	218	70	328			
	54040-18	54.0	40	68	222	70	332			
	54540-18	54.5	40	68	222	70	332			
	55040-18	55.0	40	68	226	70	336			
	55540-18	55.5	40	68	226	70	336			
	56040-18	56.0	40	68	230	70	342	SPMT180510-PD XOMT180508-PD	FTNA0511	TW20-100
	56540-18	56.5	40	68	230	70	342			
	57040-18	57.0	40	68	235	70	347			
	57540-18	57.5	40	68	235	70	347			
	58040-18	58.0	40	68	240	70	352			
	58540-18	58.5	40	68	240	70	352			
	59040-18	59.0	40	68	245	70	357			
	59540-18	59.5	40	68	245	70	357			
	60040-18	60.0	40	68	250	70	362			
	60540-18	60.5	40	68	250	70	362			

KING DRILL-5D





(mm)

Designatón	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K5D 12020-04	12.0	20	25	63	50	127	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
12520-04	12.5	20	25	63	50	127			
13020-04	13.0	20	25	68	50	132			
13520-04	13.5	20	25	68	50	132			
14020-05	14.0	20	25	73	50	138			
14520-05	14.5	20	25	73	50	138			
15020-05	15.0	20	25	78	50	144			
15520-05	15.5	20	25	78	50	144			
16020-05	16.0	20	25	83	50	149	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
16525-06	16.5	25	34	83	56	155			
17025-06	17.0	25	34	88	56	160			
17525-06	17.5	25	34	88	56	160			
18025-06	18.0	25	34	93	56	166			
18525-06	18.5	25	34	93	56	166			
19025-06	19.0	25	34	98	56	171			
19525-06	19.5	25	34	98	56	171			
20025-07	20.0	25	34	103	56	178	SPMT060205-PD XOMT060204-PD	FTKA02206S	TW07P
20525-07	20.5	25	34	103	56	178			
21025-07	21.0	25	34	108	56	183			
21525-07	21.5	25	34	108	56	183			
22025-07	22.0	25	34	113	56	188			
22525-07	22.5	25	34	113	56	188			
23025-07	23.0	25	34	118	56	195			
23525-07	23.5	25	34	118	56	195			
24032-09	24.0	32	44	123	60	205	SPMT07T208-PD XOMT07T205-PD	FTKA02565	TW07S
24532-09	24.5	32	44	123	60	205			
25032-09	25.0	32	44	128	60	210			
25532-09	25.5	32	44	128	60	210			
26032-09	26.0	32	44	133	60	215			
26532-09	26.5	32	44	133	60	215			
27032-09	27.0	32	44	138	60	221			
27532-09	27.5	32	44	138	60	221			
28032-09	28.0	32	44	143	60	227	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
28532-09	28.5	32	44	143	60	227			
29032-09	29.0	32	44	148	60	232			
29532-09	29.5	32	44	148	60	232			

KING DRILL



KING DRILL-5D



(mm)

Designatón	ØD	Ød1	Ød2	l1	l2	L	Insert	Screw	Wrech
K5D	30032-11	30.0	32	44	153	60	240	SPMT11T308-PD XOMT11T306-PD	FTKA03508
	30532-11	30.5	32	44	153	60	240		
	31032-11	31.0	32	44	158	60	245		
	31532-11	31.5	32	44	158	60	245		
	32032-11	32.0	32	44	163	60	250		
	32532-11	32.5	32	44	163	60	250		
	33032-11	33.0	32	44	168	60	256		
	33532-11	33.5	32	44	168	60	256		
	34032-11	34.0	32	44	173	60	261		
	34532-11	34.5	32	44	173	60	261		
	35032-11	35.0	32	44	178	60	266		
	35532-11	35.5	32	44	178	60	266		
	36040-13	36.0	40	48	184	70	284		
	36540-13	36.5	40	48	184	70	284		
	37040-13	37.0	40	48	189	70	289		
	37540-13	37.5	40	48	189	70	289		
	38040-13	38.0	40	48	194	70	295		
	38540-13	38.5	40	48	194	70	295		
	39040-13	39.0	40	48	199	70	300	SPMT130410-PD XOMT130406-PD	FTKA0410
	39540-13	39.5	40	48	199	70	300		
	40040-13	40.0	40	48	204	70	306		
	40540-13	40.5	40	48	204	70	306		
	41040-13	41.0	40	48	209	70	311		
	41540-13	41.5	40	48	209	70	311		
	42040-13	42.0	40	48	214	70	317		
	42540-13	42.5	40	48	214	70	317		
	43040-15	43.0	40	58	220	70	325		
	43540-15	43.5	40	58	221	70	326		
FTNC04511	44040-15	44.0	40	58	225	70	330	SPMT15M510-PD XOMT15M508-PD	TW20S
	44540-15	44.5	40	58	225	70	330		
	45040-15	45.0	40	58	230	70	336		
	45540-15	45.5	40	58	230	70	336		
	46040-15	46.0	40	58	235	70	341		
	46540-15	46.5	40	58	235	70	341		
	47040-15	47.0	40	58	240	70	347		
	47540-15	47.5	40	58	240	70	347		

KING DRILL-5D





(mm)

Designatton	ØD	Ød_1	Ød_2	l_1	l_2	L	Insert	Screw	Wrech	
K5D	48040-15	48.0	40	58	245	70	352	SPMT15M510-PD XOMT15M508-PD	FTNC04511	TW20S
	48540-15	48.5	40	58	245	70	352			
	49040-15	49.0	40	58	250	70	357			
	49540-15	49.5	40	58	250	70	357			
	50040-15	50.0	40	58	255	70	362			
	50540-15	50.5	40	58	255	70	362			
	51040-18	51.0	40	68	261	70	371			
	51540-18	51.5	40	68	261	70	371			
	52040-18	52.0	40	68	266	70	376			
	52540-18	52.5	40	68	266	70	376			
	53040-18	53.0	40	68	271	70	381			
	53540-18	53.5	40	68	271	70	381			
	54040-18	54.0	40	68	276	70	386			
	54540-18	54.5	40	68	276	70	386			
	55040-18	55.0	40	68	281	70	391			
	55540-18	55.5	40	68	281	70	391			
	56040-18	56.0	40	68	286	70	398			
	56540-18	56.5	40	68	286	70	398			
	57040-18	57.0	40	68	292	70	404			
	57540-18	57.5	40	68	292	70	404			
	58040-18	58.0	40	68	298	70	410			
	58540-18	58.5	40	68	298	70	410			
	59040-18	59.0	40	68	304	70	416			
	59540-18	59.5	40	68	304	70	416			
	60040-18	60.0	40	68	310	70	422			
	60540-18	60.5	40	68	310	70	422			

KING DRILL



KING DRILL (for through coolant system with a lathe)-2D



(mm)

Designatton		ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K2D	13020HP-04	13.0	20	25	29	50	93	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	14020HP-05	14.0	20	25	31	50	96	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
	15020HP-05	15.0	20	25	33	50	99			
	16020HP-05	16.0	20	25	35	50	101	SPMT060205-PD XOMT060204-PD	FTKA02206S	TW07P
	17025HP-06	17.0	25	34	37	56	109			
	18025HP-06	18.0	25	34	39	56	112	SPMT07T208-PD XOMT07T205-PD	FTKA02565	TW07S
	19025HP-06	19.0	25	34	41	56	114			
	20025HP-07	20.0	25	34	43	56	118	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
	21025HP-07	21.0	25	34	45	56	120			
	22025HP-07	22.0	25	34	47	56	122			
	23025HP-07	23.0	25	34	49	56	126			
	24032HP-09	24.0	32	44	51	60	133			
	25032HP-09	25.0	32	44	53	60	135			
	26032HP-09	26.0	32	44	55	60	137			
	27032HP-09	27.0	32	44	57	60	140			
	28032HP-09	28.0	32	44	59	60	143			
	29032HP-09	29.0	32	44	61	60	145			

KING DRILL (for through coolant system with a lathe)-3D





(mm)

Designatton	ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech	
K3D	13020HP-04	13.0	20	25	42	50	106	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	13520HP-04	13.5	20	25	42	50	106			
	14020HP-05	14.0	20	25	45	50	110			
	14520HP-05	14.5	20	25	45	50	110			
	15020HP-05	15.0	20	25	48	50	114			
	15520HP-05	15.5	20	25	48	50	114			
	16020HP-05	16.0	20	25	51	50	117			
	16525HP-06	16.5	25	34	51	56	123			
	17025HP-06	17.0	25	34	54	56	126			
	17525HP-06	17.5	25	34	54	56	126			
	18025HP-06	18.0	25	34	57	56	130			
	18525HP-06	18.5	25	34	57	56	130			
	19025HP-06	19.0	25	34	60	56	133			
	19525HP-06	19.5	25	34	60	56	133			
	20025HP-07	20.0	25	34	63	56	138			
	20525HP-07	20.5	25	34	63	56	138			
	21025HP-07	21.0	25	34	66	56	141			
	21525HP-07	21.5	25	34	66	56	141			
	22025HP-07	22.0	25	34	69	56	144			
	22525HP-07	22.5	25	34	69	56	144			
	23025HP-07	23.0	25	34	72	56	149			
	23525HP-07	23.5	25	34	72	56	149			
	24032HP-09	24.0	32	44	75	60	157			
	24532HP-09	24.5	32	44	75	60	157			
	25032HP-09	25.0	32	44	78	60	160			
	25532HP-09	25.5	32	44	78	60	160			
	26032HP-09	26.0	32	44	81	60	163			
	26532HP-09	26.5	32	44	81	60	163			
	27032HP-09	27.0	32	44	84	60	167			
	27532HP-09	27.5	32	44	84	60	167			
	28032HP-09	28.0	32	44	87	60	171			
	28532HP-09	28.5	32	44	87	60	171			
	29032HP-09	29.0	32	44	90	60	174			
	29532HP-09	29.5	32	44	90	60	174			

KING DRILL


KING DRILL (for through coolant system with a lathe)-4D



(mm)

Designatton		ØD	Ød1	Ød2	l ₁	l ₂	L	Insert	Screw	Wrech
K4D	13020HP-04	13.0	20	25	55	50	119	SPMT040204-PD XOMT040204-PD	FTNA0204	TW06P
	14020HP-05	14.0	20	25	59	50	124	SPMT050204-PD XOMT050204-PD	FTNA0204	TW06P
	15020HP-05	15.0	20	25	63	50	129			
	16020HP-05	16.0	20	25	67	50	133	SPMT060205-PD XOMT060204-PD	FTKA02206S	TW07P
	17025HP-06	17.0	25	34	71	56	143			
	18025HP-06	18.0	25	34	75	56	148	SPMT07T208-PD XOMT07T205-PD	FTKA02565	TW07S
	19025HP-06	19.0	25	34	79	56	152			
	20025HP-07	20.0	25	34	83	56	158	SPMT090308-PD XOMT090305-PD	FTKA0307	TW09S
	21025HP-07	21.0	25	34	87	56	162			
	22025HP-07	22.0	25	34	91	56	166			
	23025HP-07	23.0	25	34	95	56	172			
	24032HP-09	24.0	32	44	99	60	181			
	25032HP-09	25.0	32	44	103	60	185			
	26032HP-09	26.0	32	44	107	60	189			
	27032HP-09	27.0	32	44	111	60	194			
	28032HP-09	28.0	32	44	115	60	199			
	29032HP-09	29.0	32	44	119	60	203			

KING DRILL (for large diameter drilling)



(mm)

Designatton	ØD	Ød1	Ød2	l1	l2	L	Cartridge		Screw	Wrech
							Insert	Insert		
K2D	616550-11	61~65	50	80	130	85	260	KDC6165C	KDC6165P	FTKA03508
	657050-13	65~70	50	88	140	85	270	KDC6570C	KDC6570P	FTKA0410
	707550-13	70~75	50	88	150	85	280	KDC7075C	KDC7075P	FTKA0410
	758050-13	75~80	50	88	160	85	290	KDC7580C	KDC7580P	FTKA0410
	808550-15	80~85	50	88	170	85	300	KDC8085C	KDC8085P	FTNC04511
	859050-15	85~90	50	95	180	85	310	KDC8590C	KDC8590P	FTNC04511
	909550-15	90~95	50	95	190	85	320	KDC9095C	KDC9095P	FTNC04511
	9510050-18	95~100	50	95	200	85	330	KDC95100C	KDC95100P	FTNA0511
K3D	616550-11	61~65	50	80	195	85	325	KDC6165C	KDC6165P	FTKA03508
	657050-13	65~70	50	88	210	85	340	KDC6570C	KDC6570P	FTKA0410
	707550-13	70~75	50	88	225	85	355	KDC7075C	KDC7075P	FTKA0410
	758050-13	75~80	50	88	240	85	370	KDC7580C	KDC7580P	FTKA0410
	808550-15	80~85	50	88	255	85	385	KDC8085C	KDC8085P	FTNC04511
	859050-15	85~90	50	95	270	85	400	KDC8590C	KDC8590P	FTNC04511
	909550-15	90~95	50	95	285	85	415	KDC9095C	KDC9095P	FTNC04511
	9510050-18	95~100	50	95	300	85	430	KDC95100C	KDC95100P	FTNA0511
K4D	616550-11	61~65	50	80	260	85	390	KDC6165C	KDC6165P	FTKA03508
	657050-13	65~70	50	88	280	85	410	KDC6570C	KDC6570P	FTKA0410
	707550-13	70~75	50	88	300	85	430	KDC7075C	KDC7075P	FTKA0410
	758050-13	75~80	50	88	320	85	450	KDC7580C	KDC7580P	FTKA0410
	808550-15	80~85	50	88	340	85	470	KDC8085C	KDC8085P	FTNC04511
	859050-15	85~90	50	95	360	85	490	KDC8590C	KDC8590P	FTNC04511
	909550-15	90~95	50	95	380	85	510	KDC9095C	KDC9095P	FTNC04511
	9510050-18	95~100	50	95	400	85	530	KDC95100C	KDC95100P	FTNA0511

• Parts

Cartridge		Range (Ø)	Insert				Screw	Wrench
Internal	External		Designation	Quantity	Designation	Quantity		
KDC6165C	KDC6165P	61 ~ 65	XOM(E)T11T306-□□	2	SPM(E)T11T308-□□	2	FTKA03508	TW15S
KDC6570C	KDC6570P	65 ~ 70	XOM(E)T130406-□□	2	SPM(E)T130410-□□	2	FTKA0410	TW15S
KDC7075C	KDC7075P	70 ~ 75	XOM(E)T130406-□□	2	SPM(E)T130410-□□	2	FTKA0410	TW15S
KDC7580C	KDC7580P	75 ~ 80	XOM(E)T130406-□□	2	SPM(E)T130410-□□	2	FTKA0410	TW15S
KDC8085C	KDC8085P	80 ~ 85	XOM(E)T15M508-□□	2	SPM(E)T15M510-□□	2	FTNC04511	TW20S
KDC8590C	KDC8590P	85 ~ 90	XOM(E)T15M508-□□	2	SPM(E)T15M510-□□	2	FTNC04511	TW20S
KDC9095C	KDC9095P	90 ~ 95	XOM(E)T15M508-□□	2	SPM(E)T15M510-□□	2	FTNC04511	TW20S
KDC95100C	KDC95100P	95 ~ 100	XOM(E)T180508-□□	2	SPM(E)T180510-□□	2	FTNA0511	TW20-100



Head Office

Holystar B/D, 1350, Nambusunhwan-ro, Geumcheon-gu, Seoul, 153-823, Korea

Tel : +82-2-522-3181 Fax : +82-2-522-3184, +82-2-3474-4744

Web : www.korloy.com E-mail : export@korloy.com

Cheongju Factory

55, Sandan-ro, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 361-290, Korea

Tel : +82-43-262-0141 Fax : +82-43-262-0146

Jincheon Factory

54, Gwanghyewonsandan 2-gil, Gwanghyewon-myeon, Jincheon-gun, Chungcheongbuk-do, 365-831, Korea

Tel : +82-43-535-0141 Fax : +82-43-535-0144

R & D Institute

55, Sandan-ro, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 361-290, Korea

Tel : +82-43-262-0141 Fax : +82-43-262-0711



620 Maple Avenue, Torrance, CA 90503, USA

Tel : +1-310-782-3800 Toll Free : +1-888-711-0001 Fax : +1-310-782-3885

www.korloyamerica.com E-mail : sales@korloy.us



Heinrich-Lanz-Allee 12, 60437 Frankfurt am Main, Germany

Tel : +49-69-5069-887-0 Fax : +49-69-5069-887-29

www.korloyeurope.com E-mail : sales@korloyeurope.com



Ground Floor, Property No. 217, Udyog Vihar Phase 4, Gurgaon 122016, Haryana, INDIA

Tel : +91-124-4050030 Fax : +91-124-4050032

www.korloyindia.com E-mail : sales.kip@korloy.com



Av. Aruana 280, conj.12, WLC, Alphaville, Barueri, CEP06460-010, SP, Brasil

Tel : +55-11-4193-3810

E-mail : vendas@korloy.com

www.korloy.com

- Please refer to stock management of cutters and detail dimensions in the 2014~2015 catalogue.



20150430

TN02-EM-01